

Certificate of Conformity of the Factory Production Control 1213–CPR–018

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product(s)

O.C.-Plan 1015, 1018, 1020, 1025, 1030, black	1,5 mm, 1,8 mm, 2,0 mm, 2,5 mm, 3,0 mm
O.C.-Plan 1015, black with silver coated surface	1,5 mm
O.C.-Plan 1018, black with silver coated surface	1,8 mm
O.C.-Plan 1020, black with silver coated surface	2,0 mm
O.C.-Plan 1025, black with silver coated surface	2,5 mm
O.C.-Plan 1030, black with silver coated surface	3,0 mm
O.C.-Plan 3018, 3020, 3025, 3030, black	1,8 mm, 2,0 mm, 2,5 mm, 3,0 mm
O.C.-Plan 4230, black	2,0 mm
O.C.-Plan 5028 SK, black	2,0 mm

Flexible sheets for waterproofing - Plastic damp proof sheets including plastic basement tanking sheets made of Ethylene Copolymer Bitumen (ECB) or of flexible polyolefins (FPO)

O.C.-Plan FCM 2015 v, Colour 1,5 mm

Flexible sheets for waterproofing - Plastic damp proof sheets including plastic basement tanking sheets made of Ethylene Copolymer Bitumen (ECB), reinforced with glass nonwoven

Intended use: damp proof sheets TYPE A and basement tanking sheets TYPE T

placed on the market under the name or trade mark of

POLYFIN AG

Polyfinstraße 1
74909 Meckesheim

and produced in the manufacturing plant(s)

0015

This certificate attests that all provisions concerning the assessment and verification of constancy of performance (AVCP) described in Annex ZA of the standard(s)

EN 13967:2012

under system 2+ are applied and that

**the factory production control is assessed to be
in conformity with the applicable requirements.**

This certificate was first issued on 2006-10-18 and will remain valid as long as neither the harmonised standard(s), the construction product(s), the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body.

Würzburg, 17 January 2018



i. V.

Dipl.-Ing. Helmut Zanzinger
Certification Body

Certificate of Conformity of the Factory Production Control 1213–CPR–018

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product(s)

Polyfin® 1020, Colour (et al. light grey, grey, black, red, green, blue, white)	2,0 mm
Polyfin® 3015, Colour (et al. light grey, grey, black, red, green, blue, white)	1,5 mm
Polyfin® 3016, 3016 FR Colour (et al. light grey, grey, black, red, green, blue, white)	1,6 mm
Polyfin® 3016 SP-M, Colour (et al. blue, light blue, white)	1,6 mm
Polyfin® 3018, 3018 FR Colour (et al. light grey, grey, black, red, green, blue, white)	1,8 mm
Polyfin® 3020, 3020 FR Colour (et al. light grey, grey, black, red, green, blue, white)	2,0 mm
Polyfin® 3023, Colour (et al. light grey, grey, black, red, green, blue, white)	2,3 mm
Polyfin® 3025, Colour (et al. light grey, grey, black, red, green, blue, white)	2,5 mm
Polyfin® 3030, Colour (et al. light grey, grey, black, red, green, blue, white)	3,0 mm
Polyfin® FCM 4012 v, Colour (et al. light grey, grey, black, red, green, blue, white)	1,2 mm
Polyfin® 4015 v, Colour (et al. light grey, grey, black, red, green, blue, white)	1,5 mm
Polyfin® 4016 v, Colour (et al. light grey, grey, black, red, green, blue, white)	1,6 mm
Polyfin® 4018 v, Colour (et al. light grey, grey, black, red, green, blue, white)	1,8 mm
Polyfin® 4020 v, Colour (et al. light grey, grey, black, red, green, blue, white)	2,0 mm
Polyfin® 4120 PP, Colour (et al. light grey)	1,8 mm
Polyfin® 4230, Colour (et al. light grey, grey, black, red, green, blue, white)	2,0 mm
Polyfin® 5024 SK, Colour (et al. light grey, grey, black, red, green, blue, white)	1,6 mm
Polyfin® 5028 SK, Colour (et al. light grey, grey, black, red, green, blue, white)	2,0 mm
Atlantic® 301, Colour (et al. light grey, grey, black)	2,0 mm
Atlantic® 401, Colour (et al. light grey, grey, black)	2,0 mm

Flexible sheets for waterproofing - Plastic damp proof sheets including plastic basement tanking sheets made of Ethylene Copolymer Bitumen (ECB) or of flexible polyolefins (FPO)

Intended use: damp proof sheets TYPE A and basement tanking sheets TYPE T

placed on the market under the name or trade mark of

POLYFIN AG
 Polyfinstraße 1
 74909 Meckesheim

and produced in the manufacturing plant(s)

0015

This certificate attests that all provisions concerning the assessment and verification of constancy of performance (AVCP) described in Annex ZA of the standard(s)

EN 13967:2012

under system 2+ are applied and that **the factory production control is assessed to be in conformity with the applicable requirements.**

This certificate was first issued on 2006-10-18 and will remain valid as long as neither the harmonised standard(s), the construction product(s), the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body.



(Handwritten signature)
 i. V.

Dipl.-Ing. Helmut Zanzinger
 Certification Body

Würzburg, 17 January 2018